

Kingma KMAPRINTER 5.5 Specifications:

Print head: mirco piezo dot-on-demand print head (Epson the 5th generation)
2 print heads
4 color: C M Y K
Height adjustable range: 2-5mm

Resolution (Maximum): 1440 dpi

Printing width (maximum): 1.88 m

Printing speed: Draft mode: 540 *720 dpi 39 sq.m./h
Production mode: 720 * 720 dpi: 24 sq.m./h
High quality model: 720 * 1440 dpi: 11 sq.m./h

Heating system: Front, middle, back three sections heating sytem,
PID temperature controller
Adjustable range: room temperature ~ 80 Celsius degree

Drying system: Outer var-speed fan

Media: Max. width: 1.88 m
Media handling system: Auto media feeding, manual media releasing
Media type: Adhesive Vinyl, PVC, Mesh, Textile,
Banner, Eco solvent inkjet paper etc...

Inks: KMAPRINTER 5.5 eco solvent pigment inks
Ink Cartridge: 350 ml, 8 pieces

RIP KMAPrint Professional Bi-language RIP(Chinese & English)
Form: Tiff, Jpeg etc
PostScript file interpreter (optional)

Driver: KMAPRINTER 5.5 Professional bi-language software (Chinese & English)

Data port: USB 2.0, RS 232

Working system: Windows XP

Input Power: AC 220-240V 50/60 HZ
1000W (max. power) 300W(working power)

Working environment: Temperature: 20-25
Humidity: 40-70%, non condensation

Physical specifications Printer dimension: (L*W*H) : 2.84*0.9*1.25 m (with stand)
Packing dimension: (L*W*H) :3*0.93*0.73 m (with stand)
Net weight: 150 KG (with stand)
Gross weight: 240 KG (with stand)